

## DHP – HDPE HALF-PIPE

DS 120 E 0405



# DHP - HDPE HALF PIPE

Technical Data

**Colored Polyethylen Sheathing for durable corrosion protection and design of non grouted Stay Cable Bridges**

Kind of Duct	Splitted HDPE double wall half-pipe with click connection Design optimized by FEM static calculation for strongest climate conditions as temperature, wind, hurricanes and rain.																																																					
UV Stability	Best UV-stability / color stability																																																					
Heat Resistance	Best heat resistance to reduce “aging due to heat” effect																																																					
Micro Crack Resistance	Best stabilisation to reduce formation of micro fissures at pipe surface																																																					
Pressure Tightness	Splash Water tight only																																																					
Sizes	<table><tr><td>OD</td><td>ID</td><td>WallOD/cavity /Wall ID</td><td>OD</td><td>ID</td><td>WallOD/cavity /Wall ID</td><td>OD</td><td>ID</td><td>WallOD/cavity /Wall ID</td></tr><tr><td>90</td><td>62</td><td>4/7/3</td><td>160</td><td>132</td><td>4/7/3</td><td>250</td><td>220</td><td>5/6/4</td></tr><tr><td>110</td><td>82</td><td>4/7/3</td><td>180</td><td>152</td><td>4/7/3</td><td>280</td><td>250</td><td>5/6/4</td></tr><tr><td>125</td><td>97</td><td>4/7/3</td><td>200</td><td>172</td><td>4/7/3</td><td>315</td><td>285</td><td>5/6/4</td></tr><tr><td>140</td><td>112</td><td>4/7/3</td><td>225</td><td>195</td><td>5/6/4</td><td>355</td><td>325</td><td>5/6/4</td></tr></table>									OD	ID	WallOD/cavity /Wall ID	OD	ID	WallOD/cavity /Wall ID	OD	ID	WallOD/cavity /Wall ID	90	62	4/7/3	160	132	4/7/3	250	220	5/6/4	110	82	4/7/3	180	152	4/7/3	280	250	5/6/4	125	97	4/7/3	200	172	4/7/3	315	285	5/6/4	140	112	4/7/3	225	195	5/6/4	355	325	5/6/4
OD	ID	WallOD/cavity /Wall ID	OD	ID	WallOD/cavity /Wall ID	OD	ID	WallOD/cavity /Wall ID																																														
90	62	4/7/3	160	132	4/7/3	250	220	5/6/4																																														
110	82	4/7/3	180	152	4/7/3	280	250	5/6/4																																														
125	97	4/7/3	200	172	4/7/3	315	285	5/6/4																																														
140	112	4/7/3	225	195	5/6/4	355	325	5/6/4																																														
Colors	More than 200 colors incl. metallic effect colors available.																																																					
Installation and Jointing	Half-pipes to be clicked together longitudinal over installed strand bundles. For best performance of half-pipes ID, we recommend to add 16-20 mm installation gap all in all to max OD of stands/packers. Radial joints by butt welding with special half-pipe welding equipment available for all sizes.																																																					
Production	For product no norm available. Production with ISO 9001 Quality Plan.																																																					
Material	High Density Polyethylen with density of 0.95 g/cm3 at 23°C acc ASTM D 3350 class 345444 E. Color contains special color and stabilization compound created by us.																																																					
Chemical Resistance	Against almost any type of chemical attack.																																																					
UV – Tests	20.000 hours Xenotest 1200 and W-O M test (corresponding to 20 years realtime in Middle Europe) do not visible show any change in color or fading in the color. The appearance of the surface remains unchanged. Very slow progress of structural material changes in confirmed. NOCX-pipes estimate for best product performance for more than 50 years. (Result of test report of famous independent laboratory.)																																																					
UV – Stability Guarantee	We offer 15 years guarantee on color stability and mechanical properties.																																																					
Fittings	Top fixing of half-pipes to steel anchors with special HDPE connectors to be clamped with special stainless steel clamps.																																																					
Prefabrication	We offer job site assistance and service in the field.																																																					
Options	DHPS Halfpipe system for grouted cable protection after stressing or repair.																																																					
References	On request.																																																					

**Contact us for more details.**

Discover PESTEC. Discover our ideas.

contact@pes-tec.com

www.pes-tec.com