

CIC 1 PVC ANCHOR DUCT

DS 410 E 0704



CIC 1 PVC ANCHOR DUCT

Technical Data

Corrugated PVC Duct system for excellent corrosion protection of permanent ground anchors.

Kind of Duct Thick wall corrugated plastic duct with circular corrugations and incorporated screw coupler

Norm No norms available

Material PVC acc DIN 7748 with K-value 66 in color black or yellow

Chemical Resistance Against almost any type of chemical attack

Sizes

Sizes in mm				
Model	OD	ID	Wall	Pipe Length
R 50	50,1	43,4	1,5	4950
R 56	55,9	50,8	1,0	5200
R 65	65,1	57,0	1,0	5200
R 80	79,7	71,4	1,0	5200
R 100	100,0	90,0	1,0	5200

Duct Length All sizes available in straight length standard 5,2 m only.

Advantages

- High durability and exp. service life of 50 years
- Safe and stiff pipe system
- Good chemical resistance
- Good mechanical resistance (abrasion and impact resistance, low fractures)
- Flexible
- Easy to handle (low weight)
- Temperature resistance (-20° to +80°C)

Jointing

- Incorporated screw coupler
- Heat shrink sleeve

Fittings Spacer, High-pressure injection pipes, Port vents, Vent pipes, Valves, End caps and Shrink sleeve couplers with or without mastic available.

Options

- Smooth PVC Anchor Pipes to fit with CIC 1 PVC Anchor pipe system
- PES CIC 2 HDPE Anchor Pipes with circular corrugations
- PES SIC 2 HDPE Anchor pipes with sinusoidal corrugations
- PES SPC HDPE Anchor Pipes with spiral corrugated corrugations.

Contact us for more details.

Discover PESETEC. Discover our ideas.