

## CIC 1 PVC ANCHOR DUCT

DS 410 E 0704



# CIC 1 PVC ANCHOR DUCT

Technical Data

DS 410 E 0704

**Corrugated PVC Duct system for excellent corrosion protection of permanent ground anchors.**

**Kind of Duct** Thick wall corrugated plastic duct with circular corrugations and incorporated screw coupler

**Norm** No norms available

**Material** PVC acc DIN 7748 with K-value 66 in color black or yellow

**Chemical Resistance** Against almost any type of chemical attack

**Sizes**

Sizes in mm				
Model	OD	ID	Wall	Pipe Length
R 50	50,1	43,4	1,5	4950
R 56	55,9	50,8	1,0	5200
R 65	65,1	57,0	1,0	5200
R 80	79,7	71,4	1,0	5200
R 100	100,0	90,0	1,0	5200

**Duct Length** All sizes available in straight length standard 5,2 m only.

**Advantages**

- High durability and exp. service life of 50 years
- Safe and stiff pipe system
- Good chemical resistance
- Good mechanical resistance (abrasion and impact resistance, low fractures)
- Flexible
- Easy to handle (low weight)
- Temperature resistance (-20° to +80°C)

**Jointing**

- Incorporated screw coupler
- Heat shrink sleeve

**Fittings** Spacer, High-pressure injection pipes, Port vents, Vent pipes, Valves, End caps and Shrink sleeve couplers with or without mastic available.

**Options**

- Smooth PVC Anchor Pipes to fit with CIC 1 PVC Anchor pipe system
- PES CIC 2 HDPE Anchor Pipes with circular corrugations
- PES SIC 2 HDPE Anchor pipes with sinusoidal corrugations
- PES SPC HDPE Anchor Pipes with spiral corrugated corrugations.

**Contact us for more details.**

Discover PESETEC. Discover our ideas.