


<p><b><u>PFS Coupler</u></b></p> <p>Push-Fit coupler including sealing rings for duct connection. Pressure tightness 0,5 bar. Compliance to FIB bulletin report 7 recommendation and FDOT</p>	
<p><b><u>PF Coupler</u></b></p> <p>Smooth Push Fit Coupler for straight connections. Suitable to use with heat shrink pipe coupler or heat shrink sleeve coupler for electrical duct isolation.</p>	
<p><b><u>Grout Ports</u></b></p> <p>Professional fast and easy connection weld to duct for connection of grout tubes. Welding with small welding equipment pressure tight. Available for HDPE and PP.</p>	
<p><b><u>Grout Port Welding Equipment</u></b></p> <p>Professional fast and easy welding of grout ports to ducts for grout tube connections. Available 220V and 110V.</p>	
<p><b><u>Heat Shrink Pipe Coupler</u></b></p> <p>Heat shrink pipe thick walled with special glue for longitudinal force-locked duct connection and duct to anchorage connection</p>	
<p><b><u>Heat Shrink Sleeve Coupler</u></b></p> <p>Heat shrink sleeve thin walled with special glue for pipe connection or suitable with PF coupler for electrical duct isolation.</p>	
<p><b><u>SB-Coupler</u></b></p> <p>PE Coupler for Plastic Duct connection of precast elements in segmental bridges</p>	

<p><b><u>PT Accessoires</u></b></p> <p>Grout vents, vent pipe, vent pipe coupler, end caps, grout valves and more available. Please ask for detailed information</p>	
<p><b><u>PESTEC Gel Epoxy</u></b></p> <p>Viscoelastic Gel of Epoxy Polymer for advanced and durable protection of post tensioning applications</p>	