


<p><b><u>Buttwelding</u></b></p> <p>Buttwelding of pipes using buttwelding equipment for pipe to pipe connection.</p>	
<p><b><u>PFS Coupler</u></b></p> <p>Push-Fit coupler including sealing rings for duct connection. Pressure tightness 0,5 bar. Compliance to FIB bulletin report 7 recommendation and FDOT</p>	
<p><b><u>PF Coupler</u></b></p> <p>Smooth Push Fit Coupler for straight connections. Economic and fast connection non pressure tight. Suitable to use with heat shrink sleeve coupler for electrical duct isolation.</p>	
<p><b><u>Heat Shrink Pipe Coupler</u></b></p> <p>Heat shrink pipe thick walled with special mastic for longitudinal force-locked duct connection and duct to anchorage connection</p>	
<p><b><u>Heat Shrink Sleeve Coupler</u></b></p> <p>Heat shrink sleeve thin walled with special hot melt for pipe connection.</p>	
<p><b><u>Heat Shrink Sleeve Coupler on PF coupler</u></b></p> <p>Heat shrink sleeve thin walled with special hot melt suitable with PF coupler for electrical duct isolation.</p>	
<p><b><u>SB-Coupler</u></b></p> <p>PE Coupler for Plastic Duct connection of pre-cast elements in segmental bridges</p>	