

TI 243-1

**SIZE LIST PMSL HDPE HEAT SHRINK PIPE
Coupler**

**EDITION 0714
PAGE 1/1**

PMSL HDPE Heat Shrink Pipe Coupler Information

Product Spec.	Shrinkable with hot air (pressure tightness 0,1 bar) or flame (pressure tightness 0,8 bar)
Material	HDPE colour black incl. glue of 80 mm inside both ends
Standard length	200 mm
Special length	Other length on request
Packing	Each coupler packed in protection foil
Storage	Max storage temperature should not exceed 40°C

IP-4 PMSL HDPE Heat Shrink Pipe Coupler with Glue

Duct Size ID/max OD	Duct Size OD/max OD	HSP Coupler Size Type	Heat Shrink Pipe coupler ID before shrinkage	HSP Coupler Wall	HSP Coupler Nominal min shrinkage ID
mm	mm	mm	mm	mm	mm
58/74	63/74	63/77	77	3.0	63
76/92	81/92	75/95 S1	95	3.0	75
85/101	91/101	90/104	104	3.0	90
100/116	106/116	110/125	125	3.0	106
115/131	121/131	125/140	140	3.0	121
130/146	137/146	140/155	155	3.0	137
140/157	147/157	140/162 S1	162	3.0	140
150/167	157/167	160/175	175	3.0	155

The named nominal minimum shrinkage ID is the guaranteed value which might be up to 3 mm lower at perfect conditions.