

SPC HDPE ANCHOR DUCT

DS 450 E 0704



SPC HDPE ANCHOR DUCT

Technical Data

Corrugated HDPE Duct system for excellent corrosion protection of permanent ground anchors.

Kind of Duct Thick wall corrugated plastic duct with spiral corrugations.

Norm No norms available

Materials Polyethylen acc ASTM D 3350 PE 345444 E with density of 0,94 g/cm³ at 23°C. Color black.

Chemical Resistance Against almost any type of chemical attack

Sizes

Sizes in mm			
Model	OD	ID	Wall
50/40	50	40	2,0
55/45	55	45	2,0
60/50	60	50	2,0
65/55	65	55	2,0
70/60	70	60	2,0

Sizes in mm			
Model	OD	ID	Wall
75/65	75	65	2,0
80/70	80	70	2,0
90/80	90	80	2,5
95/85	95	85	2,5
100/90	100	90	2,5

Duct Length All sizes available in straight length standard 5,8 m or in coils. Other straight length on request.

Advantages

- High durability and exp. service life of 100 years
- Safe and stiff pipe system
- Possible to use for electrical isolated systems
- Best chemical resistance
- Best mechanical resistance (abrasion and impact resistance, low fractures)
- Slightly flexible
- Easy to handle (low weight)
- High temperature resistance (-40° to +80°C)
- Environmental friendly material, saving electric power and water during production, fuel because of low weight during transport and installation.

Jointing

- Spiral corrugated overlap coupler
- Heat shrink sleeve

Fittings

Spacer, High-pressure injection pipes, Port vents, Vent pipes, Valves, End caps and Shrink sleeve couplers with or without mastic available.

Grout Port Welding

PESTEC Grout Ports weldable directly to the duct in economic, easy, professional, safe and pressure tight way using our special welding equipment.

Options

- PES CIC 1 PVC Anchor Pipes for bar anchors.
- PES CIC 2 HDPE Anchor pipes with circular corrugations and screw coupler.
- PES SIC HDPE Anchor Pipes with sinusoidal corrugations.

Contact us for more details.

Discover PESTEC. Discover our ideas.

PESTEC GmbH, Am Limespark 2, D-65843 Sulzbach, Germany
Phone ++49 6196-76681- 0 Fax ++49 6196-76681- 20
contact@pes-tec.com www.pes-tec.com