






<p><u>Type B 1</u></p> <p>Stiff HDPE ball spacer with very good 'ball' flexibility. Spacers are splitted in 2 halves for easy installation and should be fixed at the spacer ends with tape</p>	
<p><u>Type B 2</u></p> <p>Stiff PVC ball spacer with good 'ball' flexibility. Spacers have one longitudinal length cut for more easy installation</p>	
<p><u>Type F 1</u></p> <p>7 mm HDPE flat skid spacer section to be extended with multiple sections to required pipe OD. High dimension variety by flexible fixing rakes. Minimum pipe OD 100 mm</p>	
<p><u>Type H 1</u></p> <p>25 mm HDPE high skid spacer section to be extended with multiple sections to required pipe OD. For pipe sizes OD 65 and 130 mm</p>	
<p><u>Type E</u></p> <p>Stiff PP spacer in several designs of big size variety for toughest applications. Spacers are splitted in 2 halves and fixed by plastic fastening straps or bolts. Size 20-2000 mm.</p>	
<p><u>Type F 2 and F 3</u></p> <p>10 and 15 mm HDPE flat skid spacer. 2 spacers can be used next to each other. High dimension variety by easy cutting. Minimum pipe OD 60 mm. Fixation by plastic fastening straps</p>	