












<p><u>Pressure Pipe Sockets</u></p> <p>Sockets for fast and easy pipe connections. Available for pressure and non pressure pipes 90 - 355 mm. Fair price. Non detachable.</p>	
<p><u>Push Fit Coupler (Big Size)</u></p> <p>Push fit coupler for fast and easy connection including longitudinal force lock grip. Available for pressure and non pressure pipes 90-225 mm. Fair price and non detachable.</p>	
<p><u>Push Fit Gas Coupler</u></p> <p>Push fit coupler for fast and easy connection of natural gas transportation pipelines including longitudinal force lock grip. Fair price. Non detachable.</p>	
<p><u>Push Fit Coupler (Small Size)</u></p> <p>Push fit coupler for fast and easy connection including longitudinal force lock grip. Available for pressure and non pressure pipes 32 - 90 mm. Low price and non detachable.</p>	
<p><u>Steel Grip Coupler</u></p> <p>Connection of HDPE pipes to other materials. Recommended for repair work and low pressure applications. Limited longitudinal force lock properties. High price. Detachable.</p>	
<p><u>Electrofusion Coupler Steel Thread Connection</u></p> <p>Connection of HDPE pipes to other materials. Available for high pressure applications. Perfect longitudinal force lock properties. High price. Detachable.</p>	
<p><u>Screw Coupler</u></p> <p>Screw coupler for fast and easy connection with limited longitudinal force lock properties. Available for pressure and non pressure pipes. High price. Detachable solution.</p>	

<u>HDPE/PVC Transition</u> Good longitudinal force lock properties. Available for pressure and non pressure pipes. Fair price. Detachable.	
<u>HDPE steel transition</u> Fitting needs to be weld to both pipe materials. Perfect longitudinal force lock properties. Available for pressure and non pressure pipes. Very high price. Non detachable.	
<u>Pressure Test Grip Flange</u> Temporary grip flange for HDPE pipe pressure tests. Available for pressure and non pressure pipes. High price. Detachable.	
<u>Shrink Pipe</u> Shrink pipe is heated to the pipe ends for connection. Recommended for non pressure pipe applications. Limited longitudinal force lock properties. Fair price. Non detachable.	
<u>Thread Connection</u> Connection of HDPE pipes to other materials. Recommended for low pressure applications. Good longitudinal force lock properties. High price. Detachable.	