

TI 921- 5

**SIZE LIST PMSL HDPE HEAT SHRINK PIPE
Coupler**

**EDITION 0714
PAGE 1/1**

PMSL HDPE Heat Shrink Pipe Coupler Information

Product Spec.	Shrinkable with hot air (pressure tightness 0,1 bar) or flame (pressure tightness 0,8 bar)
Material	HDPE colour black incl. glue of 80 mm inside both ends
Standard length	800 mm
Special length	Other length on request
Packing	Each coupler packed in protection foil
Storage	Max storage temperature should not exceed 40°C

IP-4 PMSL HDPE Heat Shrink Pipe Coupler with Glue

Type	Wall	ID before shrinkage	Nominal min shrinkage ID	Type S1	Wall	ID before shrinkage	Nominal min shrinkage ID	Type S2	Wall	ID before shrinkage	Nominal min shrinkage ID
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
63	3.0	77	63								
75	3.0	88	75	75	3.0	95	75				
90	3.0	104	90	90	3.0	108	90	90	5.4	120	90
110	3.0	125	107	110	3.0	128	110	110	4.2	140	110
125	3.0	140	122	125	3.0	145	125	125	4.8	155	125
140	3.0	155	138	140	3.0	162	140	140	5.4	175	140
160	3.0	175	155	160	3.2	184	160	160	6.2	196	160
180	3.5	196	177	180	3.6	202	180	180	5.5	216	180
200	3.5	216	196	200	3.6	224	200	200	6.2	242	200

The named nominal minimum shrinkage ID is the guaranteed value which might be up to 3 mm lower at perfect conditions.